according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: FLOOR OIL

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Floor finish

Details of Manufacturer or Importer:

GMR Imports

4 Bute St, Invercargill, Southland, 9810, NZ

Phone Number: 0800 800 718

Emergency telephone number: 0800 800 718

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.



Flammable Liquids 3 H226 Flammable liquid and vapour.



Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.

HSNO Classification

3.1C - Flammable liquid - medium hazard.

6.1E - Substances that are acutely toxic - May be harmful, Aspiration hazard.

Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

(Contd. on page 2)

according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

Product Name: FLOOR OIL

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

46.5%

Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1B, H350; Aspiration Hazard 1, H304; Flammable Liquids 4, H227; Acute Toxicity (Dermal) 5, H313

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eve Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Inaestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause irritation of the throat, chest tightness, coughing and wheezing.

Skin Contact: May cause skin irritation and redness.

Eye Contact: May cause eye irritation, redness and watering.

Ingestion: May cause irritation and redness to the mouth and throat. May be fatal if swallowed and enters airways.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water fog, alcohol resistant foam, dry chemical or carbon dioxide.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon and other toxic fumes.

Product is flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Closed containers may explode when exposed to extreme heat. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

(Contd. on page 3)

according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

Product Name: FLOOR OIL

(Contd. of page 2)

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Avoid the formation of mists and aerosols. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from heat, sparks, open flames, hot surfaces and direct sunlight. Keep away from strong oxidising agents and strong acids.

Suitable packaging material: Glass or coated steel.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Respiratory protection is not required under normal use conditions.

Use an approved self-contained breathing apparatus in case of emergency. See Australian Standards AS/ NZS 1715 and 1716 for more information.

Skin Protection:

Protective gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form: Liquid

Colour: Milky, range of colours.

Odour: Paraffinic

Odour Threshold: No information available

pH-Value: ~7

(Contd. on page 4)

according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

Product Name: FLOOR OIL

(Contd. of page 3)

Melting point/freezing point:No information available **Initial Boiling Point/Boiling Range:**No information available

Flash Point: 38 °C Flammability: Flammable.

Auto-ignition Temperature:No information availableDecomposition Temperature:No information available

Explosion Limits:

Lower:No information availableUpper:No information availableVapour Pressure:No information available

Relative Density at 20 °C: 0.87

Vapour Density:No information availableEvaporation Rate:No information available

Solubility in Water: Not miscible

Solubility in Solvents: Most organic solvents.

Partition Coefficient (n-octanol/water): No information available
Viscosity: 33 s (Kinematic, ISO 2431)

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials: Strong oxidising agents and strong acids.

Hazardous Decomposition Products: Toxic fumes.

11. TOXICOLOGICAL INFORMATION

Toxicity:

LD ₅₀ /LC ₅₀	Values	Relevant for	Classification:
------------------------------------	--------	--------------	-----------------

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD_{50} >5,000 mg/kg (rat) Dermal LD_{50} >3,000 mg/kg (rabbit)

Acute Health Effects

Inhalation: May cause irritation of the throat, chest tightness, coughing and wheezing.

Skin: May cause skin irritation and redness.

Eye: May cause eye irritation, redness and watering.

Ingestion:

May cause irritation and redness to the mouth and throat. May be fatal if swallowed and enters airways.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

(Contd. on page 5)

according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

Product Name: FLOOR OIL

(Contd. of page 4)

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Chronic Health Effects: No information available

Existing Conditions Aggravated by Exposure: No information available

Additional toxicological information: No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Aquatic toxicity:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

 $LC_{50}/96 \text{ h}$ 2,200 mg/l (fathead minnow) $LC_{50}/48 \text{ h}$ >1,000 ppm (golden orfe)

Persistence and Degradability: Biodegradable.

Bioaccumulative Potential: Bioaccumulation is not expected to occur.

Mobility in Soil: Readily absorbed into soil.

Other adverse effects: No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14. TRANSPORT INFORMATION

UN Number

NZS 5433 UN1263 UN1263 UN1263

Proper Shipping Name

NZS 5433 PAINT PAINT PAINT

Dangerous Goods Class

NZS 5433 3 Flammable liquids. IMDG Class: 3 Flammable liquids.

Packing Group:

NZS 5433 III IMDG, IATA III

EMS Number: F-E,S-E

Hazchem Code: 3Y

Special Provisions: 163, 223

Limited Quantities: 5L

(Contd. on page 6)

according to HSNO Act 1996

Printing date 02.10.2018 Revision: 02.10.2018

Product Name: FLOOR OIL

(Contd. of page 5)

Excepted quantities (EQ) E1

Packagings & IBCs - Packing Instruction: P001, IBC03, LP01

Packagings & IBCs - Special Packing Provisions: PP1
Portable Tanks & Bulk Containers - Instructions: T2

Portable Tanks & Bulk Containers - Special

Provisions: TP1, TP29

15. REGULATORY INFORMATION

HSNO Approval Code / Group Standard:

Surface Coatings and Colourants (Flammable) Group Standard 2017

HSNO Approval Number: HSR002662

New Zealand Inventory of Chemicals

All ingredients are listed.

16. OTHER INFORMATION

Date of Preparation or Last Revision: 02.10.2018

Prepared by: MSDS.COM.AU Pty Ltd www.msds.com.au

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit TWA: Time Weighted Average

WES: Workplace Exposure Standard

Flammable Liquids 3: Flammable liquids – Category 3 Flammable Liquids 4: Flammable liquids – Category 4 Acute Toxicity (Dermal) 5: Acute toxicity – Category 5

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B Aspiration Hazard 1: Aspiration hazard – Category 1

Disclaimer

This SDS is prepared in accord with the New Zealand Chemical Industry Council document 'Code of Practice (No. HSNO CoP 8-1 09-06)'.

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. GMR Imports makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.