

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

1 . IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: TEAK OIL

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Outdoor Wood Finish

Details of Manufacturer or Importer:

GMR Imports
4 Bute St, Invercargill,
Southland, 9810, NZ

Phone Number: 0800 800 718

Emergency telephone number: 0800 800 718

2 . HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.



flame

Flammable Liquids 3 H226 Flammable liquid and vapour.



health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.

HSNO Classification

3.1C - Flammable liquid - medium hazard.

6.1E - Substances that are acutely toxic - May be harmful, Aspiration hazard.

Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

(Contd. on page 2)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: TEAK OIL

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national regulations.

3 . COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Hazardous Components:**

CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy ⚠️ Aspiration Hazard 1, H304; Flammable Liquids 4, H227	57.647%
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy ⚠️ Aspiration Hazard 1, H304	0.241%

4 . FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing unless stuck to skin. Wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause irritation of the throat and chest tightness.

Skin Contact: May cause mild skin irritation.

Eye Contact: May cause mild eye irritation and redness.

Ingestion: May cause vomiting and diarrhoea. May be fatal if swallowed and enters airways.

5 . FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol resistant foam, dry chemical powder or carbon dioxide.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon.

Product is flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Closed containers may explode when exposed to extreme heat. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 . ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

(Contd. on page 3)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: TEAK OIL

(Contd. of page 2)

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools.

7 . HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Only store in original container. Protect from heat, sparks, open flames, hot surfaces and direct sunlight. Keep away from oxidising agents and strong acids.

8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Use an approved type A vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Protective gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 . PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Form:	Liquid
Colour:	Pale brown
Odour:	Paraffinic
Odour Threshold:	No information available
pH-Value:	No information available

(Contd. on page 4)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: TEAK OIL

(Contd. of page 3)

Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	150 - 190 °C
Flash Point:	43 °C
Flammability:	Flammable.
Auto-ignition Temperature:	No information available
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure:	No information available
Relative Density at 20 °C:	0.850
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	Insoluble
Solubility in Solvents:	Soluble in most organic solvents.
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	Non-viscous

10 . STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames, hot surfaces and direct sunlight.

Incompatible Materials: Oxidising agents and strong acids.

Hazardous Decomposition Products: Oxides of carbon.

11 . TOXICOLOGICAL INFORMATION

Toxicity:

LD₅₀/LC₅₀ Values Relevant for Classification:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD ₅₀	>5,000 mg/kg (rat)
Dermal	LD ₅₀	>3,000 mg/kg (rabbit)

Acute Health Effects

Inhalation: May cause irritation of the throat and chest tightness.

Skin: May cause mild skin irritation.

Eye: May cause mild eye irritation and redness.

Ingestion: May cause vomiting and diarrhoea. May be fatal if swallowed and enters airways.

Skin Corrosion / Irritation: Based on classification principles, the classification criteria are not met.

Serious Eye Damage / Irritation: Based on classification principles, the classification criteria are not met.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

(Contd. on page 5)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: TEAK OIL

(Contd. of page 4)

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: May be fatal if swallowed and enters airways.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

12 . ECOLOGICAL INFORMATION

Ecotoxicity:**Aquatic toxicity:****CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy**LC₅₀/96 h 2,200 mg/l (fathead minnow)LC₅₀/48 h >1,000 ppm (golden orfe)**Persistence and Degradability:** No further relevant information available.**Bioaccumulative Potential:** No further relevant information available.**Mobility in Soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.

13 . DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 . TRANSPORT INFORMATION

UN Number

NZS 5433

UN1263

IMDG, IATA

UN1263

Proper Shipping Name

NZS 5433

PAINT

IMDG, IATA

PAINT

Dangerous Goods Class

NZS 5433

3 Flammable liquids.

IMDG Class:

3 Flammable liquids.

Packing Group:

NZS 5433

III

IMDG, IATA

III

EMS Number:F-E,S-E**Hazchem Code:**

3Y

Special Provisions:

163, 223

Limited Quantities:

5L

Excepted quantities (EQ)

E1

(Contd. on page 6)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: TEAK OIL

(Contd. of page 5)

Packagings & IBCs - Packing Instruction: P001, IBC03, LP01**Packagings & IBCs - Special Packing Provisions:** PP1**Portable Tanks & Bulk Containers - Instructions:** T2**Portable Tanks & Bulk Containers - Special Provisions:** TP1, TP29

15 . REGULATORY INFORMATION

HSNO Approval Code / Group Standard:

Surface Coatings and Colourants (Flammable) Group Standard 2017

HSNO Approval Number: HSR002662

New Zealand Inventory of Chemicals

All ingredients are listed.

16 . OTHER INFORMATION

Date of Preparation or Last Revision: 02.10.2018**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percentLD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

WES: Workplace Exposure Standard

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Aspiration Hazard 1: Aspiration hazard – Category 1

Disclaimer

This SDS is prepared in accord with the New Zealand Chemical Industry Council document 'Code of Practice (No. HSNO CoP 8-1 09-06)'.

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. GMR Imports makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.