Page 1/7

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Name: WOOD DYE

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Wood dye

Details of Manufacturer or Importer: GMR Imports 4 Bute St, Invercargill, Southland, 9810, NZ

Phone Number: 0800 800 718

Emergency telephone number: 0800 800 718

2. HAZARDS IDENTIFICATION

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.



Flammable Liquids 3

H226 Flammable liquid and vapour.



Skin Corrosion/Irritation 2 H315 Causes skin irritation.

Serious Eye Damage/Irritation 2A H319 Causes serious eye irritation.

HSNO Classification

- 3.1C Flammable liquid medium hazard.
- 6.3A Substances that are irritating to the skin.
- 6.4A Substances that are irritating to the eye.

9.3C - Substances that are harmful to terrestrial vertebrates.

Signal Word Warning

Hazard Statements

H226 Flammable liquid and vapour.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

Precautionary Statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash hands thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P321 Specific treatment (see on this label).

(Contd. on page 2)

Page 2/7

SAFETY DATA SHEET according to HSNO Act 1996

Printing date 02.10.2018

Product Name: WOOD DYE

Revision: 02.10.2018

(Contd. of page 1) P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313	If skin irritation	occurs: Get medical	advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:		
CAS: 5131-66-8	3-butoxypropan-2-ol ♦ Acute Toxicity (Oral) 4, H302; Acute Toxicity (Dermal) 4, H312; Acute Toxicity (Inhalation) 4, H332; Skin Corrosion/Irritation 2, H315; Serious Eye Damage/Irritation 2A, H319; Flammable Liquids 4, H227	20.950%
CAS: 95-63-6	Benzene, 1,2,4-trimethyl- Flammable Liquids 3, H226; STOT SE 2, H371; Aquatic Chronic 2, H411; Acute Toxicity (Oral) 4, H302; Acute Toxicity (Dermal) 4, H312; Acute Toxicity (Inhalation) 4, H332; Serious Eye Damage/Irritation 2A, H319; Skin Corr. 3, H316; Aquatic Acute 2, H401	
CAS: 64742-95-6	6 Solvent naphtha (petroleum), light arom. 0	
CAS: 108-67-8	Mesitylene Flammable Liquids 3, H226; Aquatic Chronic 2, H411; Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H335; Skin Corr. 3, H316; Aquatic Acute 2, H401	0.125%

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing unless stuck to skin. Wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause irritation of the throat and chest tightness. May cause drowsiness or mental confusion. Skin Contact: Causes skin irritation and redness.

Eye Contact: Causes serious eye irritation and redness.

Ingestion: May cause vomiting and diarrhoea. May cause congestion of the lungs leading to shortness of breath.

Page 3/7

SAFETY DATA SHEET according to HSNO Act 1996

Printing date 02.10.2018

Product Name: WOOD DYE

(Contd. of page 2)

Revision: 02.10.2018

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Alcohol resistant foam, dry chemical powder or carbon dioxide. Do not use water.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon.

Product is flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Closed containers may explode when exposed to extreme heat. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Only store in original container. Protect from heat, sparks, open flames, hot surfaces and direct sunlight. Keep away from oxidising agents and strong acids.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Standards:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Use an approved type A vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

(Contd. on page 4)

Page 4/7

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Product Name: WOOD DYE

(Contd. of page 3)

Revision: 02.10.2018

Skin Protection:

Protective gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	
Form:	Liquid
Colour:	Range of colours
Odour:	Paraffinic
Odour Threshold:	No information available
pH-Value:	No information available
Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	150 - 190 °C
Flash Point:	38 °C
Flammability:	Flammable.
Auto-ignition Temperature:	No information available
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure:	No information available
Relative Density:	0.850
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	Not miscible
Solubility in Solvents:	Soluble in benzene.
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	Non-viscous

10. STABILITY AND REACTIVITY

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames, hot surfaces and direct sunlight.

Incompatible Materials: Strong oxidising agents and strong acids.

Hazardous Decomposition Products: Oxides of carbon.

(Contd. on page 5)

Page 5/7

SAFETY DATA SHEET according to HSNO Act 1996

Printing date 02.10.2018

Revision: 02.10.2018

Product Name: WOOD DYE

(Contd. of page 4)

11. TOXICOLOGICAL INFORMATION

Toxicity:

LD ₅₀ /LC ₅₀ Values Relevant for Classification:				
CAS: 95-6	CAS: 95-63-6 Benzene, 1,2,4-trimethyl-			
Oral	LD_{50}	5,000 mg/kg (rat)		
Dermal	LD₅₀	3,160 mg/kg (rabbit)		
Inhalation	LC₅₀/4 h	18 mg/l (rat)		
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral	LD₅₀	>6,800 mg/kg (rat)		
Dermal	LD₅₀	>3,400 mg/kg (rabbit)		
Inhalation	LC₅₀/4 h	>10.2 mg/l (rat)		
CAS: 108-67-8 Mesitylene				
Oral	LD_{50}	5,000 mg/kg (rat)		

Acute Health Effects

Inhalation: May cause irritation of the throat and chest tightness. May cause drowsiness or mental confusion. **Skin:** Causes skin irritation and redness.

Eye: Causes serious eye irritation and redness.

Ingestion:

May cause vomiting and diarrhoea. May cause congestion of the lungs leading to shortness of breath.

Skin Corrosion / Irritation: Causes skin irritation.

Serious Eye Damage / Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitisation: Based on classification principles, the classification criteria are not met.

Germ Cell Mutagenicity: Based on classification principles, the classification criteria are not met.

Carcinogenicity: This product does NOT contain any IARC listed chemicals.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Single Exposure:

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.

Chronic Health Effects: No information available

Existing Conditions Aggravated by Exposure: No information available

Additional toxicological information: No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity: Harmful to terrestrial vertebrates.

Aquatic toxicity:

CAS: 95-63-6 Benzene, 1,2,4-trimethyl-

LC₅₀/96 h 7.19-8.28 mg/l (fathead minnow)

(Contd. on page 6)

SAFETY DATA SHEET

according to HSNO Act 1996

Printing date 02.10.2018

Product Name: WOOD DYE

CAS: 108-67-8 Mesitylene

EC₅₀/24 h 50 mg/l (daphnia) LC₅₀/96 h 9.89-15.05 mg/l (goldfish)

Persistence and Degradability: No further relevant information available.

Bioaccumulative Potential: No further relevant information available.

Mobility in Soil: No further relevant information available. **Other adverse effects:** No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration: Please consult your state Land Waste Management Authority for more information.

14. TRANSPORT INFORMATION

I	UN Number NZS 5433 IMDG, IATA	UN1263 UN1263
I	Proper Shipping Name NZS 5433 IMDG, IATA	PAINT PAINT
I	Dangerous Goods Class NZS 5433 IMDG Class:	3 Flammable liquids. 3 Flammable liquids.
I	Packing Group: NZS 5433 IMDG, IATA	
I	EMS Number:	F-E, <u>S-E</u>
I	Hazchem Code:	3Y
ę	Special Provisions:	163, 223
	Limited Quantities: Excepted quantities (EQ)	5L E1
I	Packagings & IBCs - Packing Instruction:	P001, IBC03, LP01
I	Packagings & IBCs - Special Packing Provisions:	PP1
I	Portable Tanks & Bulk Containers - Instructions:	T2
	Portable Tanks & Bulk Containers - Special Provisions:	TP1, TP29
-		

15. REGULATORY INFORMATION

HSNO Approval Code / Group Standard:

Surface Coatings and Colourants (Flammable) Group Standard 2017 HSNO Approval Number: HSR002662

(Contd. on page 7)

Page 6/7

Revision: 02.10.2018

(Contd. of page 5)

SAFETY DATA SHEET according to HSNO Act 1996

www.msds.com.au

Printing date 02.10.2018

Product Name: WOOD DYE

All ingredients are listed.

16.OTHER INFORMATION

Date of Preparation or Last Revision: 02.10.2018

Prepared by: MSDS.COM.AU Pty Ltd

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) LC₅₀: Lethal concentration, 50 percent LD₅₀: Lethal dose, 50 percent IARC: International Agency for Research on Cancer STEL: Short Term Exposure Limit TWA: Time Weighted Average WES: Workplace Exposure Standard Flammable Liquids 3: Flammable liquids - Category 3 Flammable Liquids 4: Flammable liquids - Category 4 Acute Toxicity (Oral) 4: Acute toxicity - Category 4 Skin Corrosion/Irritation 2: Skin corrosion/irritation - Category 2 Skin Corr. 3: Skin corrosion/irritation - Category 3 Serious Eye Damage/Irritation 2A: Serious eye damage/eye irritation - Category 2A STOT SE 2: Specific target organ toxicity (single exposure) – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aspiration Hazard 1: Aspiration hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment, short-term (Acute). Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term (Chronic). Category 2

Disclaimer

This SDS is prepared in accord with the New Zealand Chemical Industry Council document 'Code of Practice (No. HSNO CoP 8-1 09-06)'.

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. GMR Imports makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.

Page 7/7

Revision: 02.10.2018

(Contd. of page 6)